microlin cooper
EST 1902
Hand and Respiratory Catalogue
microlincooper.co.uk

Contents

- 04 Welcome
- 05 Hand Protection Standards
- 08 Disposable and Chemical
- 14 General use
- 24 Thermal
- 28 Waterproof
- 31 Cut resistant gloves
- 46 Cut resistant sleeves
- 50 Puncture resistant
- 52 Needle resistant
- 54 Heat resistant
- 60 Anti-vibration
- 62 Anti-static
- 65 Food Handling
- 69 Anti-Impact
- 72 RespiratoryProtection

Welcome

Microlin Cooper began in the United Kingdom 25 years ago as family business and has since expanded into a thriving hub for health and safety.

We specialise in the supply of hand and respiratory protection. Our high quality products are supplied both in the UK and internationally. The strong relationships with our UK and overseas customers allows us to understand the world of health and safety on a global level.

We design and innovate our products to keep up with the pace of the ever changing demands of the health and safety sector. Our aim is to manufacture products which satisfy the demands required by the health and safety managers while following the needs and wants of the consumer. At Microlin Cooper we strongly believe in working with our customers in order to ensure they receive exactly what they desire.

From our own label 'Klass' to specific customer own branding, what makes Microlin Cooper unique is our flexibility. We thrive on our ability to customise our range and manufacture bespoke products according to what the customer requests.

At an extremely exciting time in the health and safety industry we know the future is full of opportunities and our doors are always open to our current and future customers who wish to discuss how we can help each other to remain competitive and unique in this market.

EN Standards: Guide to Hand Protection

EN388

12345

The European Standard EN388 covers the test requirements for safety gloves that are sold as protection against mechanical risks. It is generally accepted that the majority of occupational hand injuries are caused by cuts and abrasions, with most of the more serious injuries due to cuts.

The EN388 Standard requires gloves to be scored on a scale of 1 to 5 for blade cut resistance (with 5 being the highest score) and 1 to 4 for abrasion resistance, tear resistance and puncture resistance. The test results will vary according to the fibres, materials, stitching and coating used to make a particular glove.

A new version of the glove standard EN388: Protection against mechanical risks has been published, superseding EN388:2003. EN388:2016 - what's new?

1. Abrasion: New abrasion paper will be used on the testing
2. Cut: New EN/OSP 13997, also known as TDM -100 Testing method. Cut test will be graded with letter A-F for cut resistant glove.
3. Impact: A new test method (fail: F or pass for areas claiming impact protection)
4. A new marking with 6 performance level.

EN407

123456

Heat resistant gloves are rated according to EN407. EN407 ratings have 6 numbers, and each shows the glove's resistant to a certain type of hazard.

1) Resistance to flammability - The material is stretched and lit with a gas flame. The flame is held against the material for 15 seconds. After the gas flame is distinguished, the length of time is measured for how long the material either glows or burns.

2) Resistance to contact heat - The material is exposed to temperatures between +100°C and +500°C for 15 seconds. The length of time is then measured for how long it takes the material on the inside of the glove to increase by 10°C from the starting temperature (approx. 25°C).

3) Resistance to convective heat - The amount of time is measured for the heat from a gas flame to increase the temperature of the glove's inside material by 24°C.

4) Resistance to radiant heat - This is tested by measuring how long the glove is able to delay the transfer of heat from a radiant heat source.

5) Resistance to small splashes of molten metal - The test is based on the total number of drops of molten metal required to increase the temperature by 40°C between the inside of the glove and the skin.

6) Resistance to large splashes of molten metal - The test measures how much molten metal is required to damage material inside the glove.

European Regulation 10/2011 applies to all plastic articles or materials supplied in the EU which are intended to come into contact with food. This includes packaging that touches food and items in contact with foodstuffs during processing, such as 'food safe' gloves.

The Food Standards Agency is responsible for ensuring the public is protected against chemicals that might transfer onto food from materials they come into contact with, for example packaging and utensils. It carries out research and surveillance and uses the result of this to help enforce controls.

EN511

123

The EN511 test is a guide for protection against cold.

1) Resistance to convective cold (performance level 0 - 4)

2) Resistance to contact cold (performance level 0 - 4)

3) Permeability by water (0 or 1)

Convective cold resistance is based on the thermal insulation properties of the glove which are obtained by measuring the transfer of cold via convection.

Contact cold resistance is based on the thermal resistance of the glove material when exposed to contact with a cold object.

Water impermeability:

0 = water penetration after 30 minutes of exposure 1 = no water penetration.

EN374-2

EN374 - Giving Protection from Chemicals and Micro-Organisms

Acceptable liquid penetrate quality standards. The lower the index represents the better the quality.

Performance levels	1	2	3
AQL	4.0	1.5	0.65

EN374-3

XYZ

Chemical Protection

Breakthrough time more than 30 minutes. For at least 3 chemicals from the list below:

(XYZ represent the code letters for 3 of these chemicals for which the glove obtained more than 30 minutes breakthrough time.)

A Methanol
B Acetone
C Acetonitrile
D Dichloromethane
E Carbon disulfide
F Toluen
G Diethylamine
H Tetrahydrofuran
I Ethyl acetate
J n-Heptan
K Sodium hydroxide 40%
L Sulfuric acid 96%

Performance levels	0	1	2	3	4	5	6
AQL	<10	10	30	60	120	240	>480

EN381-7

Handling chainsaws

EN420

General requirements:

This pictogram indicates that the user has to consult the instructions for use.

The UKCA (UK Conformity Assessed) marking is a new UK product marking that is used for goods being placed on the market in Great Britain (England, Wales and Scotland). It covers most goods which previously required the CE marking, known as 'new approach' goods.

Materials and Coatings

Microlin offer a wide range of hand protection. The task at hand will determine which glove you choose. There are a number of materials and coatings used in gloves, each serving a different purpose. Below outlines some key features of the most popular materials and coatings used.

Coatings

Nitrile

- Tough and durable
- good abrasion and puncture resistance
- Stands up well to oil, grease, and liquids,

Nitrile foam

- Excellent abrasion resistance, puncture and tear.
- Provides supurb grip in wet and oily conditions.
- Excellent breathability
- Comfortable to wear

Sandy nitrile

- Offers the same benefits as a flat nitrile or a nitrile foam gloce but with even higher abrasion and strong grip due to a rougher surface.

Latex

- Ideal for use in wet environments
- Offers high elasticity and grip in comparison to other glove coatings. Crinkle latex offers outstanding grip along with abrasion and puncture resistance. NB Latex contains a protein that can cause allergic reactions in some wearers.

Polyurethane (PU)

- PU is a thin coating thus providing excellent dexterity
- Soft and stretchy properties that still provide good puncture resistance without being too bulky. Durable and flexible, making it an excellent coating for general sharp handling and assembly across multiple industries such as manufacturing, aerospace and precision assembly.

Materials

HPPE

- HPPE gloves are high-performance polyethylene gloves. HPPE fiber is knitted into some of the strongest gloves found on the market today.
- Excellent protection
- Comfortable and flexible

Nylon

- Good flexibility and sensitivity
- Durable and tough, helping to keep you safe in applications that demand handling and movement, but also a little protection too.

Kevlar

- Kevlar is for serious, high risk work. Developed by DuPont, this heat-resistant synthetic fibre offers exceptional resistance to cuts while protecting from heat, abrasion, tears and punctures, ideal for all-round, tough and risky work.

Cotton and Polyester

- Cotton is a lightweight and flexible material that offers exceptional sensitivity, making cotton gloves well suited to handling, assembly, inspection, driving and shop work based applications.
- Polyester, similar to cotton, is extremely flexible but as it is a synthetic fibre comes with more strength while being slightly more affordable. It too is best suited to applications such as handling and assembly.

Disposable & Chemical Gloves

Our range of disposable and chemical gloves offer both high quality and comfort for the user. Offering nitrile, PVC and butyl coated gloves the product range covers protection from a number of chemicals. Our gloves have been used in industries such as; food, medical, pharmaceutical and automative. The gloves are available in a range of colours including blue, black and orange and at different lengths to offer additional protection.

Peppermint

Material	Nitrile
Gauge	5.5ml thickness
Sizes Available	S-XXL
Bag/Case Quantity	100 gloves per box/1000 per case
Colour	Blue

Recommended areas of use:

Chemical, laboratory, pharmaceutical, clinical and hospital setting. Food processing and preparation. Electronics, engineering, manufacturing and automotive maintenance and repair.

Description

- These gloves are 5.5 mil in thickness and powder free. They are resistant to many acids and solvents. They are also approved for food preparation.
- Haute qualité nitrile gants jetables pas de poudre et 5.5 mil d'épaisseur.
- Alta calidad nitrilo guantes desechables sin polvo y 5.5 mils de espesor.

Bluemint

Material	Nitrile
Gauge	3.2ml thickness
Sizes Available	S-XXL
Bag/Case Quantity	100 gloves per box/1000 per case
Colour	Light blue

Recommended areas of use:

Chemical, laboratory, pharmaceutical, clinical and hospital setting. Food processing and preparation. Electronics, engineering, manufacturing and automotive maintenance and repair.

Description

- These nitrile disposable gloves are powder free and 3.2ml in thickness.
- Ces gants jetables en nitrile sont sans poudre et d'une épaisseur de 3.2 ml.
- Estos guantes desechables de nitrilo no contienen polvo y tienen 3.2 ml de grosor.

Nitro Black

Coating	Nitrile
Gauge	5.5ml thickness
Sizes Available	S-XXL
Bag/Case Quantity	100 gloves per box/1000 per case
Colour	Black

Recommended areas of use:

Chemical, laboratory, pharmaceutical, clinical and hospital setting. Food processing and preparation. Electronics, engineering, manufacturing and automotive maintenance and repair.

Description

- These black nitrile disposable gloves are powder free and 5.5ml in thickness.
- Ces gants jetables en nitrile sont sans poudre et d'une épaisseur de 5.5 ml.
- Estos guantes desechables de nitrilo no contienen polvo y tienen 5.5 ml de grosor.

Nitro Black lite

Coating	Nitrile
Gauge	3.2ml thickness
Sizes Available	S-XL
Bag/Case Quantity	100 gloves per box/1000 per case
Colour	Black

Recommended areas of use:

Chemical, laboratory, pharmaceutical, clinical and hospital setting. Food processing and preparation. Electronics, engineering, manufacturing and automotive maintenance and repair.

Description

- These black nitrile disposable gloves are powder free and 3.2ml in thickness.
- Ces gants jetables en nitrile sont sans poudre et d'une épaisseur de 3.2 ml.
- Estos guantes desechables de nitrilo no contienen polvo y tienen 3.2 ml de grosor.

- Phtalate Free
- Hypoallergenic
- ECARF

G52

Material	100% PVC
Sizes Available	S-XL
Bag/Case Quantity	5 pairs per bag/100 per case
Colour	White

Recommended areas of use:

Protection against chemical splashes, Precision work industries and Drain cleaning

Description

- Ideal for use against chemical splashes in regular or cleanroom environments. 60 cm total length. 100 percent PVC material and comes cleanroom packed to class 100.
- Idéal pour une utilisation contre les éclaboussures de produits chimiques. Totale 60 cm de longueur. 100% PVC.
- Ideal para el uso contra salpicaduras de sustancias químicas. 60cm de longitud total. Hecho de 100% PVC.

G630

Material	Nitrile coating, cotton liner
Sizes Available	L-XXL
Bag/Case Quantity	5 pairs per bag/60 per case
Colour	Blue

Recommended areas of use:

Agriculture & Viticulture, Automotive & Transportation, Chemical, Building & Construction, Fishing Work, Food Processing, Metal Production and Petrochemical Work.

Description

- The Phulax 630 is a 30 cm Nitrile glove offering protection from chemicals.
- Le Phulax 630 est un gant en nitrile de 30 cm offrant une protection contre les produits chimiques.
- El Phulax 630 es un guante de nitrilo de 30 cm que ofrece protección contra productos químicos.

EN388:2016
3121X
EN374-5
EN374-1
JKOPT
CE
Category 3

G630 Winter

Material	Nitrile coating, fleece liner
Sizes Available	S-XL
Bag/Case Quantity	5 pairs per bag/60 per case
Colour	Blue

Recommended areas of use:

Agriculture & Viticulture, Automotive & Transportation, Chemical, Building & Construction, Fishing Work, Food Processing and Petrochemical Work.

Description

The Phulax 630W is a nitrile coated glove with a fleece lining. Perfect for outdoor work in cold temperatures.

Le Phulax 630W est un gant enduit de nitrile avec une doublure en polaire. Parfait pour les travaux extérieurs par temps froid.

El guante Phulax 630W es un guante recubierto de nitrilo de color azul con un forro especial contra el frio. ideal para trabajos al aire libre o en temperaturas frías. y en uso con diferente tipos de ácidos.

General Use
Gloves

General use gloves can cover a wide range of applications including;

Warehouse tasks, construction work and general handling. Our range has been developed in order to offer protection and comfort without compromising the quality of the task at hand. The range includes PU, latex and nitrile coated gloves as well as offers low level protection from cuts.

Del 618

Coating	Polyurethane
Liner	Nylon
Gauge	18
Sizes Available	S-XXL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Blue

Recommended areas of use:

Building and construction, Food handling, Gardening and Handling oily materials.

Description

- An 18 gauge liner with a light PU coating. The glove provides excellent sensitivity.
- Un gant de jauge 18 avec un revêtement en polyuréthane. Un gant qui vous fait sentir comme vous travaillez avec les mains nues.
- Un guante de calibre 18 con un recubrimiento de poliuretano. Un guante que te hace sentir como si estuviera trabajando directamente con las manos.

Red Devil, 4X31A

Coating	PVC
Liner	Cotton
Gauge	13
Sizes Available	XL
Bag/Case Quantity	10 pairs per bag/60 per case
Colour	Red

Recommended areas of use:

Provides protection from oil, grease and many household chemicals.

Description

- A knitwrist red PVC coated glove on a cotton interlock liner. Provides protection from oil, grease and many household chemicals. The knitted wrist cuffs add extra comfort for the wearer.
- Gant enduit de PVC rouge au poignet tricoté sur une doublure en coton interlock. Fournit une protection contre l'huile, la graisse et de nombreux produits chimiques ménagers. Les poignets tricotés offrent un confort supplémentaire pour le porteur.
- Un guante de PVC rojo, recubierto con un forro de algodón flocado. Este producto proporciona protección contra aceites y grasas, y ciertos productos químicos domésticos. También es ideal para trabajos húmedos o donde existe mucha agua.

EN388:2016
3X41A

Grip and go

Coating	PVC dots
Liner	Mixed fibres
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/120 per case
Colour	Navy blue

Recommended areas of use:

Warehouse useage, Construction work, Soft cotton perfect for light handling and inspection and Automative industry.

Description

- A seamless five-finger knitted glove with a 4cm elasticated cuff and PVC dots on the palm for added Grip.
- Un gant de fibres mélangées avec du PVC dots pour une meilleure adhérence.
- Un guante de fibra se mezcla con puntos de PVC para un mejor agarre.

EN388:2016
3X41A
CE
Category 1

Pick and go

Coating	PVC dots
Liner	Cotton
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/120 per case
Colour	White with blue pvc dots

Recommended areas of use:

Warehouse use and Light industrial applications.

Description

- A 13 gauge knitted polyester glove with a polyurethane dipping on the fingertip area to protect against nicks and cuts.
- Usage général gant avec des points de PVC.
- Uso general guante con puntos de PVC.

EN388:2016
3X41A
CE
Category 1

Finger Picker

Coating	PVC dots
Liner	Cotton
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/300 per case
Colour	Navy blue

Recommended areas of use:

Warehouse use, Light industrial applications and where excellent grip is reqiured.

Description

- A half finger general use glove with PVC dots on the palm.
- Une demi-doigt usage général gant avec des points de PVC.
- A medio-dedo del guante de uso general con puntos de PVC.

EN388:2016
4X22A
CE
Category 1

Del 600

Coating	PU on fingertips
Liner	Polyester
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/300 per case
Colour	White

Recommended areas of use:

Electronics and Assembly.

Description

- A 13 gauge knitted polyester glove with a polyurethane dipping on the fingertip area to protect against nicks and cuts.
- Une demi-doigt usage général gant avec des points de PVC.
- Guante de poliéster con revestimiento de PU en las yemas de los dedos.

EN388:2016 4X42A CE Category 2

Orange grip

Coating	Crinkled latex
Liner	Cotton
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	12 pairs per bag/120 per case
Colour	Orange/Yellow

Recommended areas of use:

Outdoor work, Construction, Warehousing/handling and Cold storage.

Description

- A 13 gauge cotton liner with a crinkled latex coating. This coating gives the user excellent grip in wet and dry conditions. The back is left uncoated for ventilation.
- Une doublure de coton de calibre 13 avec un revêtement de latex plissés.
- Un forro de algodón calibre 13 con un recubrimiento de látex arrugado.

EN388:2016 2X43A CE Category 2

Black grip

Coating	Crinkle latex
Liner	Mixed fibre
Gauge	13
Sizes Available	M-XL
Bag/Case Quantity	12 pairs per bag/120 per case
Colour	Black

Recommended areas of use:

Building and construction work and Concrete & brick handling.

Description

- Mixed fibre and cotton glove made with a crinkled black latex coating on the palm and fingers of the hand. The back of the hand is uncoated to provide ventilation and avoid perspiration.
- Une doublure de coton de calibre 13 avec un revêtement de latex plissés.
- Fibra mixta guante hecho con un recubrimiento de látex negro arrugado.

EN388:2016 4X31A CE Category 2

L4001

Coating	Latex
Liner	Nylon
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Black

Recommended areas of use:

Building and construction work, Concrete & brick handling, Gardening and Handling of slippery materials.

Description

- A light,13 gauge nylon glove, with a hard wearing black latex coating on the palm and fingers of the hand. The glove is suitable for building & construction work, concrete & brick handling, gardening etc.
- Une lumière, de calibre 13 gants en nylon, avec un revêtement en latex noir résistant.
- Guante de nylon 13 de calibre ligero, con un recubrimiento de látex negro resistente.

EN388:2016 4X21A CE Category 2

Del 501

Coating	Nitrile
Liner	Nylon
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	12 pairs per bag/120 per case
Colour	Available in white or black

Recommended areas of use:

Building and construction work and Concrete & brick handling

Description

- A lightweight glove providing excellent grip in wet, dry and oily conditions. The glove is uncoated on the back for ventilation. Available in grey and black.
- Un gant en nylon avec un revêtement de nitrile pour une meilleure adhérence dans des conditions huileuses.
- Un guante de nylon con recubrimiento de nitrilo para un mejor agarre en condiciones aceitosas.

EN388:2016
3122X
CE
Category 2

Drivers Glove

Coating	Leather
Liner	Cotton Fleece (Available with or without lining)
Sizes Available	L-XL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Yellow

Recommended areas of use:

General use and driving.

Description

A hard wearing leather driver glove. This glove is soft and comfortable, yet tough and durable. Made with very soft, high quality leather. Available with or without cotton lining.

Gant de pilote en cuir. Disponible avec ou sans doublure.

Guantes de conducir de cuero. Disponible con o sin revestimiento interior.

EN388:2016
4X31A
CE
Category 2

Del 219

Coating	Polyurethane
Liner	Polyester
Gauge	13
Sizes Available	XS-XXL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Available in Black (Del219), White (Del499) and Grey (Del201)

Recommended areas of use:

For fine and delicate manipulations and assembly lines.

Description

A seamless polyester knitted glove, with a fine polyurethane coating on the palm and on the fingers. Available in black, grey and white. Also available with a nylon liner.

Un polyester gant 13 de la jauge avec un revêtement en polyuréthane.

Un guante de poliéster calibre 13 con un recubrimiento de poliuretano.

EN388:2016
4X21A
CE
Silicone Free

Del 552A

Coating	Water based PU
Liner	Nylon and spandex
Gauge	15
Sizes Available	S-XL
Bag/Case Quantity	12 pairs per bag 120 pairs per case
Colour	Black

Recommended areas of use:

Handling small parts. Assembly and maintenance. Automotive manufacturing and Transportation

Description

A comfortable and dextrous general use glove. The glove is 15 gauge with a water based foam PU coating. DMF and silcone FREE. Food safe. High abrasion and excellent grip suitable in wet or dry conditions.

Un gant confortable avec une grande dextérité. Le gant est de gauge15 avec une couche de mousse de PU à base d'eau. Ce gant est fabriqué SANS DMF ou sans silicone. Il est également approuvé pour un usage alimentaire.

Un guante confortable de uso general con mucha destreza. El guante es de galga 15 con una capa de espuma de PU a base de agua. Este guante es fabricado SIN DMF u sin silicona. Es tambien on homologado para uso alimentario.

EN388:2016
4X21A
CE
Category 2

Del 503

Coating	Nitrile
Liner	Nylon
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	12 pairs per bag/120 per case
Colour	Black

Recommended areas of use:

Building and construction work and Concrete & brick handling

Description

A lightweight glove providing excellent grip in wet, dry and oily conditions. The glove is uncoated on the back for ventilation. Available in grey and black.

Un gant en nylon avec un revêtement de nitrile pour une meilleure adhérence dans des conditions huileuses.

Un guante de nylon con recubrimiento de nitrilo para un mejor agarre en condiciones aceitosas.

EN388:2016 4X31A CE Category 2

Del 499

Coating	Polyurethane
Liner	Polyester
Gauge	13
Sizes Available	S-XXXL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	White
Colour	Available in Black (Del219), White (Del499) and Grey (Del201)

Recommended areas of use:

For fine and delicate manipulations and assembly lines.

Description

- A seamless polyester knitted glove, with a fine polyurethane coating on the palm and on the fingers. Available in black, grey and white. Also available with a nylon liner.
- Un polyester gant 13 de la jauge avec un revêtement en polyuréthane.
- Un guante de poliéster calibre 13 con un recubrimiento de poliuretano.

EN388:2016 4X31A CE Category 2

Del 201

Coating	Polyurethane
Liner	Polyester
Gauge	13
Sizes Available	XS-XXL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Grey
Colour	Available in Black (Del219), White (Del499) and Grey (Del201)

Recommended areas of use:

For fine and delicate manipulations and assembly lines.

Description

- A seamless polyester knitted glove, with a fine polyurethane coating on the palm and on the fingers. Available in black, grey and white. Also available with a nylon liner.
- Un polyester gant 13 de la jauge avec un revêtement en polyuréthane.
- Un guante de poliéster calibre 13 con un recubrimiento de poliuretano.

EN388:2016 4X31A CE Category 2

Del 505

Coating	Nitrile Foam
Liner	Nylon
Gauge	18
Sizes Available	S-XL
Bag/Case Quantity	12 pairs per bag/144 per case
Colour	Red

Recommended areas of use:

Construction, logistics, manufacturing and goods handling

Description

- An 18 gauge lightweight and dextrous glove providing good grip in dry and light oil conditions.
- Un gant léger et agile de calibre 18 offrant une bonne adhérence dans des conditions sèches et peu huileuses.
- Guante ligero con mucha destreza de 18 galgas con espuma de nitrilo en la palma que proporciona un buen agarre en condiciones aceitosas, el guante es también muy confortable.

EN388:2016 4X31A CE Category 2

T-310

Material	Latex, palm coated
Liner	Polyester
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	144 pairs per case
Colour	High Viz Yellow

Recommended areas of use:

Construction, logistics, manufacturing and goods handling.

Description

- A comfortable, 13 gauge glove, with a hard wearing black latex coating on the palm and fingers of the hand.
- Une gant confortable avec un revêtement en latex noir résistant.
- Guante 13 de calibre ligero, con un recubrimiento de látex negro resistente.

Thermal Gloves

Our popular selection of thermal gloves offer high protection in temperatures from -25 down to -150° Celsius. Thermal gloves are excellent for dark or cold environments such as; warehouses, building yards and freezers. Our range also includes water and oil resistant thermal gloves suitable for outdoor conditions or oily tasks.

Artix Winter

Coating	HPT foam rubber
Liner	Acrylic cotton
Gauge	7
Sizes Available	S-XXL
Bag/Case Quantity	5 pairs per bag/60 per case
Colour	High visability yellow

Recommended areas of use:

Dark and cold environments, warehouses, building yards and freezers.

Description

- High visibility, acrylic cotton liner with a black high grip, foamed-rubber coating. Flexible to temperatures as low as -25°C.
- Haute visibilité, doublure de coton acrylique avec un haut niveau d'adhérence noir, revêtement caoutchouc mousse. Pour des températures très froides, aussi basses que -25°C
- Alta visibilidad, forro de algodón acrílico con un alto agarre negro, revestimiento de goma espuma. Para temperaturas muy frías, tan bajas como -25°C

Cryo Leather

Coating	American cut cowhide leather
Liner	Wool, goretex
Sizes available	L-XL
Bag/Case Quantity	5 pairs per bag
Colour	Blue

Recommended areas of use:

Liquid nitrogen atmospheres, liquid oxygen atmospheres, liquid helium atmospheres, dry ice, blast freezers, walk-in freezers, cold rooms, handling supercooled materials.

Description

- For protection between -125°C and - 150°C to prevent freezer burns and frostbites in cryogenic atmospheres.
- Pour une protection entre -125°C et - 150°C pour éviter les brûlures de congélation et gelures
- Para una protección entre -125°C y - 150°C para evitar quemaduras de congelación y sabañones

EN511
X1X
EN388:2016
3X42A
CE
Category 2

Neon 7

Coating	Latex
Liner	Cotton
Gauge	7
Sizes Available	S-XL
Bag/Case Quantity	5 pairs per bag/60 per case
Colour	High Visability Yellow

Recommended areas of use:

General handling, manual handling, warehouse work and scaffolding.

Description

This glove is a 7 gauge cotton liner with a high grip, blue latex coating. Ideal for temperatures hovering around freezing indoors and outdoors.

Ce gant est une doublure de coton 7 de jauge avec une poignée haute, revêtement de latex bleu.

Este guante es un forro de algodón 7 guaje con un alto nivel de agarre, revestimiento de látex azul.

EN511
X1X
EN388:2016
2242
CE
Category 2

Neon 10

Coating	Latex
Liner	Cotton
Gauge	10
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	High Visability Yellow

Recommended areas of use:

General handling, manual handling and cable handling.

Description

A 10 gauge cotton liner with a high grip, black latex coating. Ideal for keeping hands warm in cold temperatures but maintaining dexterity.

Une doublure de coton de 10 jauge avec une poignée haute, revêtement de latex noir.

Un forro de algodón 10 calibre con un agarre alto, recubrimiento de látex negro.

EN511
011
EN388:2016
1241X
CE
EN407
X2XXXX

H2o Thermo

Coating	Latex Double Palm Coating
Liner	Brushed Piled Acrylic Liner
Gauge	10
Sizes Available	S-XXL
Bag/Case Quantity	12 Pairs per bag/72 per case
Colour	High Viz Orange

Recommended areas of use:

For work in cold regions, tasks in cold rooms or outside in cold weather conditions.

Description

This glove can be used in a below freezing environment. It prevents fatigue in a wide variety of cold conditions.

Les gants possèdent un support en molleton acrylique duveteux de jauge 10 et un revêtement en latex doublé.

Con un recubrimiento doble de látex y un revestimiento acrílico en bucle de calibre 10.

Waterproof Gloves

Our waterproof range is ideal for all water based tasks. The product range includes thermal, cut resistant and oil proof gloves perfect for handling greasy or wet objects. Our gloves keep hands completely dry offering the highest level of protection from the elements.

EN388:2016
4544D
CE
Category 2

Tek 540

Coating	Nitrile
Liner	Nylon
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	10 Pairs per bed/100 per case
Colour	Blue

Recommended areas of use:

When handling greasy or wet objects and Manufacturing.

Description

- A triple nitrile back coated cut level 5 glove with an added reinforcement patch between the thumb and index finger. Suitable for working in wet or oily environments.
- Gant de niveau 5 à triple couche de nitrile dans le dos. Convient pour travailler dans des environnements humides ou huileux.
- Un guante totalmente cubierto de nitrilo con un corte nivel 5. adecuado para trabajar en ambientes húmedos o aceitosos.

EN511
011
EN388:2016
1241X
CE
EN407
X2XXXX

H2o Thermo

Coating	Latex Double Palm Coating
Liner	Brushed Piled Acrylic Liner
Gauge	10
Sizes Available	S-XXL
Bag/Case Quantity	12 Pairs per bag/72 per case
Colour	High Viz Orange

Recommended areas of use:

For work in cold regions, tasks in cold rooms or outside in cold weather conditions.

Description

- This glove can be used in a below freezing environment. It prevents fatigue in a wide variety of cold conditions.
- Les gants possèdent un support en molleton acrylique duveteux de jauge 10 et un revêtement en latex doublé.
- Con un recubrimiento doble de látex y un revestimiento acrílico en bucle de calibre 10.

EN338
2131
CE
Category 2

H20

Coating	Latex + Foam Latex
Liner	Nylon
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	12 pairs per bag /144 per case
Colour	Blue

Recommended areas of use:

Excellent for handling wet items or working outdoors.
For example, working with cement on building sites or oil handling and general inspection jobs.

Description

- 13-gauge seamless nylon knitted liner glove with a double latex coating.
- Gant de doublure en nylon tricoté sans couture de calibre 13 avec double revêtement en latex.
- Guante totalmente recubierto de látex , con forro en polyester, el guante es fabricado sin costuras, tiene una galga 13, y posee doble revestimiento de látex. Uno que recubre el guante enteramente para proteger contra líquidos, y la segunda capa , en la palma de la mano para dar al producto más agarre.

EN388:2016
4544D
CE
Category 2

Tek 541

Coating	Nitrile
Liner	Nylon
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	10 Pairs per bed/100 per case
Colour	Blue

Recommended areas of use:

When handling greasy or wet objects and Manufacturing.

Description

- A triple nitrile back coated cut level 5 glove with an added reinforcement patch between the thumb and index finger. Suitable for working in wet or oily environments.
- Gant de niveau 5 à triple couche de nitrile dans le dos. Convient pour travailler dans des environnements humides ou huileux.
- Un guante totalmente cubierto de nitrilo con un corte nivel 5. adecuado para trabajar en ambientes húmedos o aceitosos.

Cut Resistant Gloves

Cut resistant gloves range from cut level 1-5 or A-F according to the new EN388 standards. Our cut resistant range has rapidly developed over the years solely through listening to our customers and offering innovative products designed especially for them. Microlin have developed a range to offer both high cut resistance as well as excellent dexterity, a key challenge faced by the industry.

EN388:2016
4342B
CE

Cut level B Gloves

Tek 547

Coating	Silica dots
Liner	Tsunooga
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/300 per case
Colour	Black

Recommended areas of use:

Handling shard objects where high grip is required.

Description

Lightweight black cut level 3 liner with blue silica dots. The glove provides excellent dexterity and comfort.

Il s'agit d'une très mince, niveau de noir coupé 3 doublure à pois bleus silice. Fournit la meilleure dextérité et de confort par rapport à un autre niveau de coupe 3 gant sur le marché.

Se trata de un revestimiento muy fino, nivel de corte negro 3 con puntos azules de sílice. Proporciona la mejor destreza y confort en comparación a cualquier otro nivel de corte 3 de los guantes en el mercado.

4342B
CE
Category 2

Cut level B Gloves

Tek 549-8

Coating	Polyurethane
Liner	Tsunooga
Gauge	13
Sizes Available	XS-XXL
Bag/Case Quantity	10 pairs per bag/100 or 300 per case
Colour	Black

Recommended areas of use:

Fine and delicate manipulations and handling small, sharp objects in the manufacturing process.

Description

A 13 gauge cut level 3 glove with a polyurethane coating. Available in: Grey or white coating/liner.

Un niveau de corte de guante 3 avec une récupération de poliuretano. Muy à la abrasion et la résistance au désespoir.

A nivel de corte del guante 3 con un recubrimiento de poliuretano. Muy a la abrasión y resistencia al desgarro.

EN388
4342B
CE
Category 2

Cut level B Gloves

Tek 549-1

Coating	Polyurethane
Liner	Tsunooga
Gauge	13
Sizes Available	XS-XXL
Bag/Case Quantity	10 pairs per bag/100 or 300 per case
Colour	White

Recommended areas of use:

Fine and delicate manipulations and handling small, sharp objects in the manufacturing process.

Description

A 13 gauge cut level 3 glove with a polyurethane coating. Available in: Grey or white coating/liner.

Un niveau de corte de guante 3 avec une récupération de poliuretano. Muy à la abrasion et la résistance au désespoir.

A nivel de corte del guante 3 con un recubrimiento de poliuretano. Muy a la abrasión y resistencia al desgarro.

EN388
4342B
CE
Category 2

Cut level B Gloves

Tek 549-2

Coating	Polyurethane
Liner	Tsunooga
Gauge	13
Sizes Available	XS-XXL
Bag/Case Quantity	10 pairs per bag/100 or 300 per case
Colour	Grey

Recommended areas of use:

Fine and delicate manipulations and handling small, sharp objects in the manufacturing process.

Description

A 13 gauge cut level 3 glove with a polyurethane coating. Available in: Grey or white coating/liner.

Un niveau de corte de guante 3 avec une récupération de poliuretano. Muy à la abrasion et la résistance au désespoir.

A nivel de corte del guante 3 con un recubrimiento de poliuretano. Muy a la abrasión y resistencia al desgarro.

EN388:2016
2342B
CE
Category 2

Cut level B Gloves

Tek 549-3

Coating	Polyurethane
Liner	Tsunooga(HPPE)
Gauge	15
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/300 per case
Colour	Grey

Recommended areas of use:

Component Handling, General Assembly, Electronics, Steel Handling and Tiling.

Description

This glove is a grey cut level 3 liner with a thin polyurethane coating. The liner is 15 gauge. The coating is reduced by 3 microns making it exceptionally flexible and tactile.

Ce gant est un niveau de gris de coupe 3 liner avec un revêtement en polyuréthane mince. Le revêtement est réduite de 3 microns.

Este guante es un gris liner nivel de corte 3 con una capa delgada de poliuretano. El recubrimiento se reduce de 3 micras.

EN388:2016
4342B
CE
Category 2

Cut level B Gloves

Tek Green

Coating	Nitrile Foam
Liner	HPPE
Gauge	18
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Green

Recommended areas of use:

Protection from oils, solvents and greases and protection from hydrocarbons such as petrol.

Description

An HPPE glove interwoven with 18 gauge needles for extra comfort, dexterity and a secure fit.

Le Tek Green est un gant HPPE entrelacé avec des aiguilles de jauge 18, pour plus de confort et de dextérité et un ajustement sécurisé. Il est revêtu de mousse de nitrile pour travailler dans des environnements huileux/graisseux.

El Tek Green es un guante HPPE entretejido con agujas de galga 18 para mayor comodidad y destreza y un ajuste seguro. Está revestido con espuma de nitrilo para trabajar en ambientes aceitosos/grasos.

EN388:2016
4343B
CE
Category 2

Cut level B Gloves

Tek 3000

Material	Polyurethane
Gauge	13
Sizes Available	XS-XL
Bag/Case Quantity	10 pairs per bag/120 per case
Colour	Grey

Recommended areas of use:

General manipulations, Construction areas and Handling sharp components as part of the manufacturing process.

Description

This is a cut level 3 liner with a slightly rough polyurethane coating.

Une coupe de niveau 3 gant, revêtement en polyuréthane, un gant à faible coût.

Un corte de nivel 3 guante, revestimiento de calibre 18, muy cómodo, recubrimiento de poliuretano.

EN388:2016
2341B
CE
Category 2

Cut level B Gloves

F17

Coating	Polyurethane
Liner	Tsunooga
Gauge	18
Sizes Available	XXS-XXL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Handling small and sharp components

Description

An 18 gauge glove manufactured with; Tsunooga , polyamide fibres and carbon fibres. It has a dark grey polyurethane coating and is compatible with touch screen technology.

Ce produit est un gant antistatique , coupure 3 tissé à cinq doigts calibre 18 fabriqué avec; Tsunooga, fibres de polyamide et fibres de carbone. Il a un revêtement gris foncé de polyuréthane sur la paume et sur les doigts.

Este producto es un guante tejido de cinco dedos de calibre 18 fabricado con; fibras anticortes Tsunooga, fibras de poliamida y fibras de carbon, El guante tiene una capa fina gris oscura de poliuretano en la palma y en los dedos.

EN388:2016 4442D CE Category 2

Cut level D Gloves

Tek 1000

Coating	Polyurethane
Liner	Tsunooga
Gauge	15
Sizes Available	XS-XXL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Handling sharp metals, blades or knvies and Handling sharp glass.

Description

- A cut level 4 liner with a polyurethane coating.
- Il s'agit d'un niveau de coupe 4 liner avec un revêtement en polyuréthane. Ce gant est un compromis idéal entre la sensibilité et une très bonne résistance à la coupure.
- Se trata de un trazador de líneas de corte a nivel 4, con un recubrimiento de poliuretano. Este guante es un compromiso ideal entre sensibilidad y muy buena resistencia a los cortes.

EN388:2016 4442D CE Category 2

Cut level D Gloves

Tek 1001

Coating	Polyurethane
Liner	Tsunooga
Gauge	15
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

For handling sharp components in manufacturing.

Description

- A unique cut level 4 glove with a semi- fingerless design. Offering high protection as well as some finger exposure when necessary.
- Le TEK 1001 est un niveau de coupe 4 gant avec un design semi-mitaines.
- La TEK 1001 es un nivel de corte de 4 guante con un diseño semi-sin dedos.

4544C CE Category 2

Cut level C Gloves

Crystal

Coating	Foam latex coating
Liner	HPPE
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Black

Recommended areas of use:

Construction work and glass handling

Description

- A cut level 5 glove offering excellent grip and high protection in wet and dry conditions.
- Il s'agit d'un niveau de réduction de 5 gant d'une couche de mousse de latex. Ce revêtement permet à l'utilisateur adhérence maximale dans des conditions humides et sèches.
- Este es un nivel de corte 5 guante con un revestimiento de espuma de látex. Este recubrimiento le da al usuario el máximo agarre en condiciones húmedas y secas.

EN388:2016 4542C CE Category 2

Cut level C Gloves

S900

Coating	Polyurethane
Liner	Tsoonooga
Gauge	15
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Green

Recommended areas of use:

Handling sharp components and when sensitivity and feeling is needed along with necessary protection.

Description

- A lightweight 15 gauge cut level 5 glove with a black polyurethane coating. The colour helps to identify the correct glove to use in a high risk area.
- Gant léger de calibre 15 de niveau 5 avec revêtement en polyuréthane noir. La couleur aide à identifier le bon gant à utiliser dans une zone à haut risque.
- Un guante verde de 15 galgas, nivel de corte 5, con un recubrimiento de poliuretano negro.

EN388:2016 4542C CE Category 2

Cut level C Gloves

S901

Coating	Polyurethane
Liner	Tsoonooga
Gauge	15
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	White

Recommended areas of use:

Construction

Description

- A three finger, lightweight cut level 5 glove with a polyurethane coating.
- Gant à trois doigts, coupe légère, niveau 5, avec revêtement en polyuréthane
- Un guante con los primeros tres dedos semi-cortados, con un nivel de corte 5 y recubrimiento de poliuretano En la palma.

EN388:2016 4544C CE Category 2

Cut level C Gloves

Tek 5000 Green

Coating	Polyurethane
Liner	Cut resistant fibres
Gauge	13
Sizes Available	M-XXL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Green

Recommended areas of use:

Handling of metal sheets and blades/knives, Handling sharp metal or plastic.

Description

- An economical cut level 5 glove with a smooth PU coating. Offering high; comfort, grip and protection.
- Gant de niveau 5 à coupe économique avec un revêtement PU lisse. Offre un haut niveau de confort, d'adhérence et de protection.
- Un guante económico de corte 5 con un suave revestimiento de PU.

EN388:2016 4X4C CE Category 2

Cut level C Gloves

Provir

Liner	Protecta Plus Fibres
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	Bags of 10/boxes of 100
Colour	Spotted blue

Recommended areas of use:

Suitable for Manufacturing, Material handling and general maintenance where cut resistance is an issue.

Description

- An inner cut level 5 glove offering great sensitivity and dexterity. Also suitable for use in the food industry.
- Un sous gant de coupure niveau 5 avec sensibilité et dextérité.
- Un guante de nivel 5 de corte con sensibilidad y destreza.

EN388:2016 4543C CE Category 2

Cut level C Gloves

Tek 5005D

Coating	Polyurethane
Liner	Cut resistant fibres & fibre glass
Gauge	13
Sizes Available	XS-XXL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Handling of metal sheets and blades/knives, Handling sharp metal or plastic and Glass, canning, rail-road industries

Description

- An economical cut level 5 glove. Offering high comfort, grip and dexterity.
- Un niveau de réduction de 5 gant avec revêtement en latex
- Un nivel de corte 5 guante con recubrimiento de látex

EN388:2016
4544D
CE
Category 2

Cut level D Gloves

Tek 1201

Coating	Leather on the palm
Liner	Kevlar , tsunooga
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Light grey

Recommended areas of use:

Protection from splinters, broken glass.

Description

- A high cut level 5 glove manufactured with leather and Kevlar for extra strength and protection.
- Gant de niveau 5 à coupe élevée fabriqué en cuir et Kevlar pour plus de solidité et de protection.
- Un guante de nivel de corte alto 5 fabricado con cuero en la palma ,para mayor resistencia y protección.

EN388:2016
4543C
CE
Category 2
EN407
X1XX4X

Cut level C Gloves

Tek 530

Coating	Nitrile
Liner	Cut resistant fibres
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Black

Recommended areas of use:

Offers heat and cut resistance.

Description

- A cut level 5 glove offering heat protection up to 80°C. Made with Kevlar and ExtraFlex technology.
- Un gant de niveau 5 offrant une protection contre la chaleur jusqu'à 80°C. Fabriqué avec la technologie Kevlar et ExtraFlex.
- Un guante de nivel de corte 5 que ofrece protección contra el calor hasta 80°C. Hecho con tecnología Aramida y ExtraFlex.

EN388:2016
4542C
CE
Category 2

Cut level C Gloves

Tek Blue

Coating	Nitrile Foam
Liner	HPPE and fibre glass
Gauge	15
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Blue

Recommended areas of use:

Protection from sharp blades/edges in oily, greasy or wet environments.

Description

- An extremely lightweight, 15 gauge cut level 5 Glove with a nitrile foam coating.
- Un gant de niveau 5 et de calibre 15 extrêmement léger, avec un revêtement en mousse de nitrile.
- Un guante extremadamente ligero de nivel 5, con una capa de espuma de nitrilo y tambien con un refuerzo entre el pulgar y el índice.

EN388:2016
4544C
CE
Category 2

Cut level C Gloves

Protecta Verde

Coating	Polyurethane
Liner	tsunooga
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	High Vis. Green

Recommended areas of use:

Glass handling and sharp metal handling.

Description

- A lightweight and flexible cut resistant glove with PU coating on the palm and fingers.
- Gant léger et souple, résistant aux coupures, avec revêtement polyuréthane sur la paume et les doigts
- Guante resistente a los cortes, ligero y flexible, con revestimiento de PU en la palma y los dedos.

EN388:2016
4X43 C
CE
Category 2

Cut level C Gloves

Tek 8000

Coating	Nitrile foam
Liner	cut resistant fibre with no glass fibre
Gauge	18
Sizes Available	XS-XXL
Bag/Case Quantity	10 pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Automative industry, Aerospace industry.

Description

- An extremely comfortable cut resistance glove with no fibre-glass or stainless steel fibres.
- Gant extrêmement confortable et résistant aux coupures, sans fibre de verre ni fibre d'acier inoxydable.
- Un guante de resistencia al corte extremadamente cómodo sin fibra de vidrio o fibras de acero inoxidable.

EN388:2016
354XF
CE
Category 2

Cut level F gloves

SaFood

Coating	None
Liner	HPPE
Gauge	10
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Light grey

Recommended areas of use:

Handling sharp materials in the food industry and Cutting with sharp knives.

Description

- This glove is manufactured using high strength cut resistant fibres and stainless steel fibres. It is seamless to avoid irritation and is ambidextrous.
- Ce gant est fabriqué à partir de haute résistance des fibres résistants aux coupures et de l'acier inoxydable, donnant un niveau de l'indice de coupe extrêmement élevée.
- Este es un nivel de corte 5 guante con un revestimiento de espuma de látex. Este recubrimiento le da al usuario el máximo agarre en condiciones húmedas y secas.

EN388:2016
4543C
CE
Category 2

Cut level C Gloves

Tek 2000

Coating	Crinkled Latex
Liner	HPPE
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Building & construction, Gardening and Waste collection

Description

- A cut level 5 liner with a crinkled latex coating for grip and water resistance.
- un niveau de réduction de 5 gant avec revêtement en latex.
- un nivel de corte 5 guante con recubrimiento de látex.

EN388:2016
4543F
CE
Category 2

Cut level F Gloves

Protecta Plus

Coating	Polyurethane
Liner	Tsoonooga
Gauge	13
Sizes Available	XS-XXXL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Glass industry, Canning, Railroad and Handling sharp metal sheets, glass, blades & knives.

Description

- A popular PU cut level 5 glove/rating F in the new EN388 ratings.
- Gant populaire en PU de niveau 5/classement F dans le nouveau classement EN388.
- Un popular guante anticorte con capa de PU y con un nivel de corte 5.

EN388:2016 4543F CE Category 2

Cut level F Gloves

Protecta Plus Extreme

Coating	Polyurethane
Liner	Tsoonoga
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Handling sharp metal sheets, glass, blades and knives. Glass, canning and rail road industries.

Description

- A popular PU cut level 5 glove/rating F in the new EN388 ratings. Featuring a reinforecent between the thumb and index finger.
- Gant populaire en PU de niveau 5/classement F dans le nouveau classement EN388. Doté d'un renforcement entre le pouce et l'index.
- Un popular guante anticorte con capa de PU y con corte nivel 5. Y adicionalmente, con un refuerzo entre el pulgar y el índice.

EN388:2016 4543 CE Category 2

Cut level D Gloves

F5X

Coating	PU
Liner	Tsunooga
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	Bags of 10/boxes of 300
Colour	Black

Recommended areas of use:

Car manufacturing, Assembly, Material handling, General maintenance where abrasion, cut and puncture resistance are required.

Description

- A comfortable, black PU cut 5 glove. The glove offers a secure fit to ensure high dexterity during delicate applications.
- Un gant noir confortable avec un couche de PU noir et une coupure 5.
- Un guante negro muy cómodo, con una capa de poliuretana negro el guante tiene un corte 5 .

EN388:2016 4X44F CE Category 2

Cut level F Gloves

TEK 6000

Coating	Nitrile foam
Liner	Cut resistant fibre
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	100 pairs per case
Colour	Grey

Recommended areas of use:

For handling sharp metals, blades, plastics, glass, etc. Industries: glass, canning, railroad.

Description

- The TEK 6000 is a low cost nitrile foam, letter F cut resistant glove. Offering both excellent dexterity and a high level of comfort.
- Gant populaire en mousse de nitrile de niveau 5/ classement F dans le nouveau classement EN388.
- Un popular guante anticorte con capa de espuma de nitrilo y con un nivel de corte 5.

EN388:2016 4543C CE Category 2

Cut level C Gloves

Tek 5C

Coating	Polyurethane
Liner	Tsoonooga
Gauge	13
Sizes Available	XS-XXXL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Glass industry, Canning, Railroad and Handling sharp metal sheets, glass, blades & knives.

Description

- A popular PU cut level 5 glove/rating C in the new EN388 ratings.
- Gant populaire en PU de niveau 5/classement C dans le nouveau classement EN388.
- Un popular guante anticorte con capa de PU y con un nivel de corte 5 / C.

Cut Resistant Sleeves

Alongside a large selection of cut resistant gloves Microlin offer a great range of high level cut resistant sleeves. Protective sleeves keep arms and wrists from cuts, puncture and abrasion in a variety of industries. For example; engineering, construction and automative. Our sleeves are available with or without an optional thumbhole or velcro-sleeve to prevent slipping. We also offer sleeves suitable for use in the food industry.

EN388 4X4XD CE Category 2

Premier Cuff

Liner	Tsunooga
Gauge	13
Sizes Available	One Size
Bag/Case Quantity	5 Pairs per bag/150 per case
Colour	Grey

Recommended areas of use:

Automative and steel industries

Description

A cut level 4 sleeve to protect arms and the palm of the hand. Total length is 45cm. Seamless lining and light in weight to avoid irritation.

Un niveau de coupe 4 manches pour protéger les bras et la paume de la main. La longueur totale est de 45 cm. Doublure transparente pour eviter irritacion.

A nivel de corte 4 una manga para proteger los brazos y parte de la palma de la mano. La longitud total es de 45cm. Forro sin costuras para evitar irritaciones.

EN388 4X42D CE Category 2

Cardiff Sleeve

Liner	Tsunooga
Gauge	13
Sizes Available	One Size
Bag/Case Quantity	5 Pairs per bag/300 per case
Colour	Grey

Recommended areas of use:

Automative industry

Description

A breathable, knitted sleeve offering a high degree of dexterity. Featuring a velcro cuff to ensure an excellent fit.

Est une manche tricotée respirante. La manchette offre un haut degré de dextérité ainsi qu'un brassard en velcro pour assurer le plus haut niveau de confort pour l'utilisateur.

La manga de Cardiff es una manga de punto de color gris transpirable fabricada con hilo Tsanooga. La manga ofrece un alto grado de destreza, así como un ajuste de velcro para garantizar el más alto nivel de confort para el usuario.

EN388 4X4XC CE Category 2

Oxford Sleeve

Liner	Tsunooga
Gauge	13
Sizes Available	One Size
Bag/Case Quantity	5 Pieces per bag/150 per case
Colour	Grey

Recommended areas of use:

Engineering, Construction, Assembly and Glass Handling.

Description

This sleeve is 55cm (21.6"), and long enough to give protection to the entire arm. They are elasticated at the wrist for comfort, and the fingerless design protects the palm and back of hand. The sleeves are seamless, and very light and flexible. High cut level 5 index.

Un manchette de 55cm (21,6"), et suffisamment longue pour assurer la protection de tout le bras. Niveau 5

Un manguito de 55cm (21.6"), y el tiempo suficiente para dar protección a todo el brazo. Nivel Cut 5.

EN388 4X4XC CE Category 2

Bristol Sleeve

Liner	Tsunooga
Gauge	13
Sizes Available	One Size
Bag/Case Quantity	5 per bag/150 per case
Colour	Blue

Recommended areas of use:

Automative industry, Food industry, Construction and Glass handling.

Description

A cut level 5 sleeve with a thumb hole. Seamless lining and light in weight to avoid irritation.

Une manchette anticoupure de coupe de niveau 5 avec un trou pour le pouce. Doublure transparente et légère pour éviter irratation.

Un manguito de corte de nivel 5 con un hveco para el pulgar.Forro sin costuras y luz en peso para evitar irratation.

EN388 4X4XC CE Category 2

Tek 120

Liner	Tsunooga
Gauge	13
Sizes Available	One size
Bag/Case Quantity	5 Pairs per bag/300 per case
Colour	Grey

Recommended areas of use:

Automotive, construction and manufacturing

Description

A full finger cut level 5 sleeve. Seamless lining and light in weight to avoid irritation.

Gant avec manchette Anti Coupure.

Guante con manguito anticorte y con forro ligero en et interior, para evitar irritacion. lo la

Puncture Resistant and Arc Flash Gloves

Our puncture resistant gloves offer the highest level of protection for the user due to the strong Dyneema fibres. The range is particularly popular in gardening as it protects the wearer from extremely sharp thorns. The gloves protect from sharp objects including barbed wire. The range also includes a glove for chainsaw use.

Ripeur 2

Liner	Dyneema/Inox fibres
Sizes Available	M-XXL
Bag/Case Quantity	5 Pairs per bag/50 per case
Colour	Beige

Recommended areas of use:

Handling in oily and greasy conditions. Can be resistant to punctures from certain syringes. Litter collection, outdoor work.

Description

The Ripeur 2 glove is fully protected on the whole hand and front of the wrist. It is made with a heavy weight, knitted cut resistant fibre and stitched with Kevlar thread. The outer layer is leather which has been treated for water resistance.

Ripeur 2 est résistant aux épines acérées et verre. Très souple et confortable à porter.

Guante muy resistente a elementos, hidrófugo. Ideal contra para uso de recoger basura, vidio etc.

Arc Flash Glove

Coating	Micro Foam
Gauge	13
Sizes Available	Small - XXL
Bag/Case Quantity	12 pairs per bag/120 per case
Colour	Green/Black

Recommended areas of use:

Oil processing and refining, electric and gas utilities, automotive industry, construction and mining

Description

Arc flash glove with superb protection from flame, heat and cut. ARC Cal rating 10.3 and cut resistant letter D.

Gant anti-arc avec une excellente protection contre les flammes, la chaleur et les coupure.

Guante de arco eléctrico con excelente protección contra llamas, calor y cortes.

Needle Resistant Gloves

Our Needle resistant gloves are ideal when the user is at risk of punctures from the likes of needles, pins, spikes and similar. Our Needle proof gloves are excellent for inspection and comes in two forms. One version offers protection all over the hand whist the second was developed to offer more dexterity for the user but still offers protection on the palm and fingertips.

EN388:2016
3544

Search Lite

Coating	Leather
Liner	Kevlar, lycra
Sizes Available	M-XL
Bag/Case Quantity	100 Pairs per bag/100 per case
Colour	Black

Recommended areas of use:

Protection from against needles, nails, splinters, glass. in industries such as Construction, Security, Inspection, Hospitals, Council Work, Gardening.

Description

The searchlite is made with a very tightly woven kevlar material called SharkSkin. Protection is on the palm and fingers.

Le gant fabriqué avec un materiau en aramide trés entroitment tisse appele 'SharkSkin. La protection est sur la paceme et doights.

Guante fabricado con un material de aramida llamado 'SharkSkin', protege la palma de la mano y los dedos.

EN388:2016
3X44F

Anti - Needle 5

Coating	Crinkled latex coating
Liner	Polyester lining, strainless steel fibres and cotton
Sizes Available	M-XL
Bag/Case Quantity	Packed per pair
Colour	Orange

Recommended areas of use:

Security inspection, hospitals, council workers, agricultural and gardening, waste disposal, construction sites, recycling areas etc.

Description

A fully waterproof anti-needle glove offering both cut and puncture protection from from hazardous objects. E.g. nails, wire, glass fragments, metal shards, wood splinters and needles.

Un gant entièrement enduit pour la protection contre les aiguilles et les échardes. La protection est sur la paceme et doights.

Un guante totalmente recubierto para la protección de agujas y astillas. Protege la palma de la mano y los dedos.

Heat Resistant Gloves

Heat resistant gloves are unarguably needed in many industries. We have a selection of heat gloves offering protection from high temperatues ranging from 350 up until 1000 degrees Celsius. Our heat gloves are popular in the steel, foundry and automative industries for example. Heat gloves are tested according to; 1. burning behaviour 2. contact heat 3. connective heat 4. radiant heat 5. small splashes of molten metal 6. high splashes of molten metal.

EN388
2442 D
CE
Category 3
EN407
43xxxx

Heatresist

Material	Palm: Para-aramid loop pile Back of hand: split cowhide leather
Gauge	Thickness: 1.2mm
Sizes Available	Medium-XXL
Bag/Case Quantity	5 pairs per bag
Colour	Grey/black/Yellow.

Recommended areas of use:

Handling of hot and cutting parts, Boiler works, Foundry, Metalworker, Maintenance.

Description

- This glove enables the user to handle items up to 350°C for up to 15 seconds.
- Les Gants Heatresist permettent à l'utilisateur de gérer les éléments jusqu'à 350°C pendant 15 secondes.
- Los Guantes Heatresist permiten al usuario manipular objetos de hasta 350°C durante un máximo de 15 segundos.

EN388
4144
CE
Category 3
EN407
413234

Silver

Material	Split cowhide with fire retardant treatment, PREOX. The lining is a mixture of wool and cotton.
Sizes Available	L-XXL
Bag/Case Quantity	5 Pairs per bag
Colour	Silver/Orange

Recommended areas of use:

Protection against radiant or contact heat and Splashes of molton metal.

Description

- This glove is excellent against splashes of molten metal, and convective and radiant heat. It has a contact temperature resistance of around 100°C for up to 15 seconds.
- Excellente contre les projections de métal en fusion, et par convection et par rayonnement thermique. Il a une résistance à la température de contact de 100°C pendant jusqu'à 15 secondes.
- Excelente contra salpicaduras de metal fundido, y convectivo y radiante de calor. Tiene una resistencia a la temperatura de contacto de 100°C durante un máximo de 15 segundos.

EN388 4343 CE Category 3 EN407 44xxxx

Hot Glove

Material	Cotton, Nomex & Kevlar
Sizes Available	One Size
Bag/Case Quantity	Per pair
Colour	Yellow

Recommended areas of use:

Handling hot products and Household uses: e.g BBQ'S.

Description

- Can withstand handling temperatures of up to 350°C for under 15 seconds. Made with Kevlar for cut resistance, and has a criss-cross silica pattern on the front and back for grip.
- Peut résister à la manutention des températures allant jusqu'à 350°C pendant moins de 15 secondes. Fabriqué avec kevlar et de silice pour une meilleure adhérence.
- Puede soportar el manejo de temperaturas de hasta 350°C durante menos de 15 segundos. Hecho con kevlar y sílice para un mejor agarre.

EN388 3544 CE Category 3 434211 EN420

Abi-800

Material	Glass fabric, twaron felt and silicone fibres.
Sizes Available	L-XXL
Bag/Case Quantity	Per pair
Colour	Yellow

Recommended areas of use:

Foundry, Holding hot plates and Handling molten metal.

Description

- The ABI-800 offers protection from temperatures up to around 800°C. This glove has achieved the maximum result in all 6 of the EN407 test standards (level 4).
- L'ABI-800 offre une protection contre les températures jusqu'à 800 °C environ. Ce gant a obtenu le meilleur résultat dans les 6 normes de test EN407 (niveau 4).
- El ABI-800 ofrece protección contra temperaturas hasta 800 ° C. Este guante ha logrado el máximo resultado en los 6 niveles de ensayo EN407 (nivel 4).

EN388 244x CE Category 2 EN407 442xxx

Long Hot Glove

Material	Inner layer: Cotton Outer layer: Kevlar and Nomex
Sizes Available	One size
Bag/Case Quantity	Per pair
Colour	Yellow

Recommended areas of use:

For added protection on lower arm when handling hot objects.

Description

- The long hot glove is a two layer glove to protect the hand and lower arm from burns. The 45cm glove offers protection from temperatures reaching 250°C.
- Un gant pour un maximum de 250°C, protège le bras et les mains.
- Un guante para un máximo de 250°C, protege la parte inferior del brazo y las manos.

EN388 2x4x CE Category 3 EN407 44xxxx

B7 Verd

Material	Mitten and cuff made with VEROST fabric.
Sizes Available	One Size
Bag/Case Quantity	Per pair
Colour	Light Green

Recommended areas of use:

Glass or steel industry., Foundary, Handling hw

Description

- The B7 very is resistant to heat contact, fire and flames up to 800°C. The total length is 40cm including 15cm cuff. It is also available in 60cm.
- Résistant au feu Mitt Pour 800°C.
- Résistant au feu Mitt Pour 800°C.

EN388
4444D
CE
Category 3
EN407
44334x

Boston Glove

Material	Split cowhide with fire retardant treatment and kevlar lining.
Sizes Available	L-XXXXL
Bag/Case Quantity	Per pair
Colour	Grey

Recommended areas of use:

Welding and Usage for protection against radiant and contact heat.

Description

- The grey boston glove is a cut level 4 welding glove manufactured with split cowhide and kevlar.
- Le gant boston glove gris est un gant de soudage de niveau 4 fabriqué en peau de vache fendue et en kevlar.
- Un guante de flor de vacuno con un forro interior hecho de kevlar, que quiere decir este producto puede ofrecer un corte 4.

EN388:2016
4244x
CE
EN407
41324X
EN12477:
Type A

Splitweld

Material	Split cowhide leather and lined with para-aramid yarn.
Sizes Available	S-XXL
Bag/Case Quantity	10 pairs per bag/50 per case
Colour	Orange/grey

Recommended areas of use:

Foundary and Hot parts handling, resistance to small molten metal projections. Spot welder.

Description

- The glove offers heat protection up to 100 degrees celcius. The glove also offers protection on the forearm due to 15cm cuff.
- Le gant offre une protection thermique jusqu'à 100 degrés Celsius. Le gant offre également une protection sur l'avant-bras grâce à une manchette de 15 cm.
- El guante ofrece protección térmica hasta 100 grados celcius. El guante también ofrece proteccion en el antebrazo debido al maguito de 15cm.

EN388:2016
4144
CE
Category 3
EN407
413243

Silverite

Material	Thermobest (TM)
Sizes Available	L-XXL
Bag/Case Quantity	Per pair
Colour	Silver

Recommended areas of use:

Heat exposure

Description

- Alumanised heat resistant glove capable of withstanding heat of up to 500 degrees.
- Gant aluminisé résistant à la chaleur, capable de résister à une chaleur allant jusqu'à 500 degrés.
- Guante para protección contra el calor radiante, y con el dorso aluminizado, hasta 350 grados.

EN388:2016
3533X
CE
Category 3
EN407
433124

S5

Coating	Silicone
Liner	Aramid
Sizes Available	9 & 10
Bag/Case Quantity	Per pair
Colour	Black/silver

Recommended areas of use:

Activities that involve contact with hot pans, trays or other tools out of ovens.

Description

- A 5-finger glove entirely in para-aramid fabric with silicone coating. The heat glove is lightweight with excellent dexterity. The lint free fabric does not absorb oil, grease or steam. Protects from contact heat up to 350 C.
- Gant à 5 doigts entièrement en tissu para-aramide avec revêtement en silicone. Le gant thermique est léger et offre une excellente dextérité. Le tissu non pelucheux n'absorbe pas l'huile, la graisse ni la vapeur. Protège de la chaleur de contact jusqu'à 350 °C.
- Un guante de 5 dedos completamente ideal para uso con productos alimentarios, el exterior es hecho con revestimiento de silicona. El guante es ligero y ofrece excelente destreza.

Anti-Vibration Gloves

Anti vibration gloves are worn to enhance absorption of strong tremors emitted through hand held heavy machinery or equipment. Wearing anti-vibration gloves reduces the chance of hand-arm vibration syndrome (HAVS) which can affect those who frequently operate powered hand tools. Available in a full finger or half fingered version the gloves work by cushioning the impact of transmitted reverberations.

EN338
x243
CE
Category 2

Anti-Vibe

Coating	Chloroprene
Liner	Cotton and polyamid fibres
Gauge	10
Sizes Available	9 & 10
Bag/Case Quantity	10 pairs per bag
Colour	Black

Recommended areas of use:

Jack hammers, Sanding, Machine Ramming and Power tools.

Description

This glove is economical and comfortable to wear, and provides good protection against shock and vibrations from machinery. Knitted with a mixture of cotton and polyamid fibres, with a Black Chloroprene coating on the palm and fingers.

Ce gant est économique et confortable à porter, et offre une bonne protection contre les chocs et les vibrations de machines.

Este guante es económico y cómodo de llevar, y ofrece una buena protección contra los golpes y las vibraciones de la maquinaria.

Anti-Static Gloves

Our Anti-static gloves have been designed for particle sensitive and low-contaminate environments. The gloves are a comfortable fit and offer high protection to the user. Some uses of anti-static gloves include automotive, Paint Line, Electronics, Cleanroom and Parts Assembly. When working in electronics assembly, gloves are worn with the intention of keeping oils from the skin off the circuit boards.

Del 300

Liner	Nylon with carbon filaments
Gauge	13
Sizes Available	S-XL
Bag/Case Quantity	10 pairs per bag /300 per case
Colour	White

Recommended areas of use:

Micro-processors, Delicate and precise operations, Electronics and Photographic printing.

Description

These lint free, nylon antistatic gloves feature integral carbon filaments to create an excellent, fitted antistatic glove. These gloves are compatible with touch screen technology. Also available with copper filaments.

Un revêtement anti-statique avec des filaments de carbone. Compatible avec l'écran tactile.

Un revestimiento antiestático con filamentos de carbono. Compatible con la pantalla táctil.

Del 310

Coating	PU on fingertips
Material	Nylon with carbon filaments
Gauge	13
Sizes Available	XXS-XXL
Bag/Case Quantity	10 pairs per bag /300 per case
Colour	White

Recommended areas of use:

Static electricity protection, Cleanrooms and Circuit boards.

Description

Lint free, nylon, antistatic glove featuring integral carbon filaments. Added PU coating on fingertips for grip. Also compatible with touch screen technology.

Un revêtement anti-statique avec des filaments de carbone, avec le bout des doigts de polyuréthane. Compatible avec l'écran tactile.

Un revestimiento antiestático con filamentos de carbono, con la punta de los dedos de poliuretano. Compatible con la pantalla táctil.

EN388:2016

CE
Category 1

EN1149

Del 320

Coating	Polyurethane
Material	Nylon carbon antistatic
Gauge	13
Sizes Available	XXS-XXL
Bag/Case Quantity	10 pairs per bag /300 per case
Colour	Light Grey

Recommended areas of use:

Indoor, Cleanrooms, Static electricity protection and Circuit boards.

Description

A lint free, nylon, antistatic glove featuring integral carbon filaments. It is palm coated and compatible with touch screen technology. Additionally, the secure fit ensures maximum dexterity for the user.

Un revêtement antistatique avec des filaments de carbone, avec le paume de polyuréthane. Compatible avec l'écran tactile.

Un revestimiento antiestático con filamentos de carbono, con la palma de poliuretano. Compatible con la pantalla táctil.

Food Handling Gloves

All of our food safe gloves follow the European standard "Food contact Application" (CE1935/2004). Our range varies from high cut protection to oil and water resistant. Some suitable uses include cutting foods with a sharp knife or handling wet/oily fish or meats.We also offer a selection of nitrile disposable gloves which offer extremely high sensitivity to the user whilst handling food.

EN388:2016
4121X
CE
Silicone Free

Del 552A

Coating	Water based PU
Liner	Nylon and spandex
Gauge	15
Sizes Available	XS-XXL
Bag/Case Quantity	12 pairs per bag 120 pairs per case
Colour	Black

Recommended areas of use:

Handling small parts. Assembly and maintenance. Automotive manufacturing and Transportation

Description

- A comfortable and dextrous general use glove. The glove is 15 gauge with a water based foam PU coating. DMF and silcone FREE. Food safe. High abrasion and excellent grip suitable in wet or dry conditions.
- Un gant confortable avec une grande dextérité. Le gant est de gauge15 avec une couche de mousse de PU à base d'eau. Ce gant est fabriqué SANS DMF ou sans silicone. Il est également approuvé pour un usage alimentaire.
- Un guante confortable de uso general con mucha destreza. El guante es de galga 15 con una capa de espuma de PU a base de agua. Este guante es fabricado SIN DMF u sin silicona. Es tambien on homologado para uso alimentario.

2000X
EN374-5
EN374-1
KMPT
CE
Category 3

- Phtalate Free
- Hypoallergenic
- ECARF

G52

Material	100% PVC
Sizes Available	S-XL
Bag/Case Quantity	5 pairs per bag/100 per case
Colour	White

Recommended areas of use:

Protection against chemical splashes, Precision work industries and Drain cleaning

Description

- Ideal for use against chemical splashes in regular or cleanroom environments. 60 cm total length. 100 percent PVC material and comes cleanroom packed to class 100.
- Idéal pour une utilisation contre les éclaboussures de produits chimiques. Totale 60 cm de longueur. 100% PVC.
- Ideal para el uso contra salpicaduras de sustancias químicas. 60cm de longitud total. Hecho de 100% PVC.

Peppermint

Material	Nitrile
Gauge	5.5ml thickness
Sizes Available	S-XXL
Bag/Case Quantity	100 gloves per box/1000 per case
Colour	Blue

Recommended areas of use:

Chemical, laboratory, pharmaceutical, clinical and hospital setting. Food processing and preparation. Electronics, engineering, manufacturing and automotive maintenance and repair.

Description

- These gloves are 5.5 mls in thickness and powder free. They are resistant to many acids and solvents. They are also approved for food preparation.
- Haute qualité nitrile gants jetables pas de poudre et 5 mil d'épaisseur.
- Alta calidad nitrilo guantes desechables sin polvo y 5 mils de espesor.

Bluemint

Material	Nitrile
Gauge	3.2ml thickness
Sizes Available	S-XXL
Bag/Case Quantity	100 gloves per box/1000 per case
Colour	Light blue

Recommended areas of use:

Chemical, laboratory, pharmaceutical, clinical and hospital setting. Food processing and preparation. Electronics, engineering, manufacturing and automotive maintenance and repair.

Description

- These nitrile disposable gloves are powder free and 3.2ml in thickness.
- Ces gants jetables en nitrile sont sans poudre et d'une épaisseur de 3.2 ml.
- Estos guantes desechables de nitrilo no contienen polvo y tienen 3.2 ml de grosor.

EN388:2016
3S4XF
CE
Category 2

Cut level 5 Gloves

SaFood

Coating	None
Liner	HPPE
Gauge	10
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Light grey

Recommended areas of use:

Handling sharp materials in the food industry and Cutting with sharp knives.

Description

This glove is manufactured using high strength cut resistant fibres and stainless steel fibres. It is seamless to avoid irritation and is ambidextrous.

Ce gant est fabriqué à partir de haute résistance des fibres résistants aux coupures et de l'acier inoxydable, donnant un niveau de l'indice de coupe extrêmement élevée.

Este es un nivel de corte 5 guante con un revestimiento de espuma de látex. Este recubrimiento le da al usuario el máximo agarre en condiciones húmedas y secas.

Anti-Impact Gloves

Our popular impact range offers high protection from impact, shock and vibration whilst handling heavy duty machinery or equipment. Our range was designed to offer the user protection whilst still maintaining high dexterity and comfort. All our gloves are manufactured with protection on the knuckles and the back of the hand.

EN388:2016
4543 F

Protecta Plus Impact

Coating	Polyurethane
Liner	Tsoonoga
Gauge	13
Sizes Available	S-XXL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Grey

Recommended areas of use:

Aerospace industry and Heavy duty applications.

Description

- Cut level 5 anti-impact gloves with thermo-plastic foam rubber patches on back of hand for protection.
- Gants anti-impact de niveau 5 avec des patchs en caoutchouc mousse thermo-plastique sur le dos des mains pour la protection.
- Guante de nivel 5, con protección contra impactos en el dorso.

EN388:2016
4342B

Impact 18

Coating	Polyurethane
Liner	Tsoonooga
Gauge	18
Sizes Available	S-XL
Bag/Case Quantity	10 Pairs per bag/100 per case
Colour	Available in Light blue or Orange

Recommended areas of use:

Aerospace industry, automotive industry, baggage handling and general lifting.

Description

- Cut level 3 anti-impact gloves with thermo-plastic foam rubber patches on back of hand for protection.
- Gants anti-impact de niveau 3 avec des patchs en caoutchouc mousse thermo-plastique sur le dos des mains pour la protection.
- Guante de nivel 3, con protección contra impactos en el dorso.

EN388:2016
314x

Impact Pick & Go

Coating	Palm: PVC dots Back: thermo- plastic foam rubber patches
Liner	Nylon
Gauge	10
Sizes Available	9 & 10
Bag/Case Quantity	10 pairs per pack 100 per case
Colour	High Visability Yellow

Recommended areas of use:

For airports - baggage handling and Warehousing

Description

- High-visability anti-impact gloves with thermo- plastic foam rubber patches on back of hand for protection.
- Gants anti-impact haute visibilité avec des patchs en caoutchouc mousse thermo-plastique sur le dos des mains pour la protection.
- Guantes anti-impacto de alta visibilidad.

Respiratory Protection

Introduction to respiratory at Microlin Cooper

The respiratory range at Microlin Cooper began in 2017 and has been expanding ever since.

The range includes FFP1, FFP2 and FFP3 disposable masks.

In addition to FFP masks, Mircolin also supply Type IIR high quality surgical masks. Microlin were one of the first businesses to bring high quality surgical masks in to the UK and Europe when the corona pandemic began. Along with our FFP3 masks these were approved for use in hospitals and by first responders.

FFP masks.

Generally, the most widely used FFP mask is an FFP3, this is because they provide the highest level of protection (filtering >99% of the air).

FFP3 masks offer a high level of protection against dangerous particulates, viruses and radioactive contamination. All our FFP3 face masks are EN149:2001 quality standard providing an assigned protection value (APF)20 and 50 NPF protection. This provides protection against fine particulates, solid aerosols or liquid aerosols listed as toxic as low as 0.3 microns. (virus size).

Face fit testing

We **strongly** encourage getting your mask face-fit tested in order to ensure you are being protected from any toxic environments. If your mask does not fit properly this can cause **serious** longterm health problems.

The purpose of a face fit test is to ensure there is a secure seal around the face in order to fully protect the user from hazardous substances in the air.

Our FFP3 disposable masks have performed outstandingly on face-fit and received high praise from expert Fit2Fit accredited face fit testers.

The ‘Air’ range and the ‘ultra’ range

The **Air** range was the first range of masks we developed at MC. Our primary focus on these masks was face fit pass rates. All these masks are premium quality and perform outstandingly on face-fit testing.

The **Ultra** range is our latest range of FFP masks. Similarly to our **Air** range the **ultra** masks are made using high quality materials and performs very well on face-fit testing. The key differences between the two ranges are that the ultra range is lower in cost and includes valved and un valved FFP2 masks.

Air 3000

Product description and key features.

The Air 3000 is a premium quality FFP3 moulded cupped mask with a valve.

Key features

1. Large exhalation valve
2. Metal Free
3. Inner foam face seal
4. Preformed nose bridge - reducing the need for frequent adjustment
5. Protection against harmful and toxic substances
6. Manufactured using high quality materials
7. Adjustable headstraps

Applications

- Woodworking
- Weldingwork
- Cutting and Casting of Metals
- Hospital
- Laboratory and Disease Control
- Textile Work
- Craft Work
- Iron and Steel Industry
- Mining
- UndergroundCivil
- Engineering
- Pharmaceutical Industry
- Disposal of Toxic Waste
- Manufacture of Batteries

Certification

EN149:2001 + A1:2009
UKCA

Packaging

10 pieces per inner box,
200 pieces per carton.

Air 3000 carbon

Product description and key features.

The Air 3000 carbon is a premium quality FFP3 moulded cupped mask with a carbon filter.

Key features

1. Large valve for easy breathing
2. Added carbon layer helps filter out nuisance levels of ozone and organic vapours
3. Metal free
4. 4 adjustable straps for a better face fit
5. Full foam inner face seal
6. Moulded nose bridge – provides the wearer an easy comfortable fit. There's no metal noseband to adjust, and the seal is maintained with less pressure.

Applications

- Woodworking
- Weldingwork
- Cutting and Casting of Metals
- Hospital
- Laboratory and Disease Control
- Textile Work
- Craft Work
- Iron and Steel Industry
- Mining
- UndergroundCivil
- Engineering
- Pharmaceutical Industry
- Disposal of Toxic Waste
- Manufacture of Batteries

Certification

EN149:2001 + A1:2009
UKCA

Packaging

10 pieces per inner box, 200 pieces per carton.

Air Sigma ∑

Product description and key features.

The Air Sigma is a new disposable FFP3V mask with mesh on the outer part of the mask.

Key features

1. Exhalation Valve – reduces moisture and heat inside the mask
2. Full face seal
3. Fully adjustable head strap enhances excellent fit
4. Mesh shell increases shape retention and durability
5. Metal-free respirator
6. Nose clip-free: pre-formed shape removes need for regular adjustment

Applications

- Woodworking
- Weldingwork
- Cutting and Casting of Metals
- Hospital
- Laboratory and Disease Control
- Textile Work
- Craft Work
- Iron and Steel Industry
- Mining
- UndergroundCivil
- Engineering
- Pharmaceutical Industry
- Disposal of Toxic Waste
- Manufacture of Batteries

Certification

EN149:2001 + A1:2009
UKCA

Packaging

10 pieces per inner box,
200 pieces per carton.

Ultra 200

Product description and key features.

The ultra 200 is a high quality FFP2 mask without a valve. The ultra 200 helps protect the wearer from airborne hazardous contaminants by filtering particles from the inhaled air.

An un-valved respirator gives the protection of both a respirator and a surgical mask.

Key features

1. Cup shaped FFP2 mask
2. Soft inner foam face seal for added comfort and a more secure face-fit.
3. Adjustable straps - helps to provide a more secure feel and provide comfort to face, head and neck.
4. Certified EN 149:2001+A1:2009/ UKCA
5. Lower cost than valved respirators

Packaging

15 masks per box

Certification

EN149:2001 + A1:2009
UKCA

Applications

- Industrial
- Factories
- Schools
- Retail
- Offices
- Healthcare

Ultra 200V

Product description and key features.

The ultra 200v is a high quality FFP2 mask with an exhalation valve. The ultra 200V helps protect the wearer from airborne hazardous contaminants by filtering particles from the inhaled air.

The valve makes it easier for the wearer to breathe and prevents heat building up in the mask.

Key features:

1. Cup shaped FFP2 mask
2. Soft inner foam face seal for added comfort and a more secure face-fit.
3. Adjustable straps - helps to provide a more secure feel and provide comfort to face, head and neck.
4. Exhalation Valve – reduces moisture and heat inside the mask

Packaging

15 masks per box

Certification

EN149:2001 + A1:2009
UKCA

Applications

- Pharmaceutical
- Shipbuilding
- Chemical processing
- Construction
- Metal processing

Ultra 300V

Product description and key features.

The ultra 300v offers the highest level of FFP protection. The added valve makes it easier for the wearer to breathe.

Key features:

1. High quality exhalation valve - minimises exhalation resistance, moisture and heat are easily expelled.
2. Inner foam face seal for better face fit and comfort
3. Metal nose clip
4. High protection against harmful and toxic substances such as fine dust, smoke and aerosols.
5. Manufactured using high quality materials
6. Adjustable head-straps - suitable for different head sizes.

Packaging

15 masks per box

Certification

EN149:2001 + A1:2009
UKCA

Applications

- Construction
- Pharmaceutical Manufacturing
- Metalworking
- Agricultural Production
- General Manufacturing
- Woodworking
- Chemical Processing
- Petrochemical
- Pharmaceuticals

Unit 12 Bourne End
Mills Industrial Estate
Upper Bourne End Ln
Tel: +44 (0) 1442 870 530
Fax: +44 (0) 1442 875 968

sales@microlincooper.co.uk
www.microlincooper.co.uk